

Model	"A"	"B"	"C"	"D"	"E"	"F"	"G"	CUBIC YARDS	MOTOR H.P.	PUMP	CYLS	CYL BORE INCHES	CYL STROKE INCHES	MAX PSI	RAM FACE SQ. IN	RAM FACE PSI	CYL FORCE LBS.	CYCLE TIME SEC	CU. YD HOUR	IND CRITERIA RATING	BASE UNIT WEIGHT LBS
SSC-4260	30	36	55	91	16	106.5	15	.75	10	12	1	6	46	2,000	960	58.9	56,540	40.5	55.1	.62	3,900
SSC-4660	44.5	52	86.75	136.25	23.5	156.75	20	1	10	15.9	1	6	68	2,000	960	58.9	56,540	45.1	73.4	.92	5,950
SSC-4660-2	44.5	52	83.75	136.25	23.5	156.75	20	1	15	19	2	6	68	2,000	960	118	113,100	75.6	43.8	.92	6,450
SSC-5060	51	57	85	141.5	16	156.75	15	1.25	10	13	1	6	68	2,000	960	58.9	56,540	55.2	68.5	1.05	4,620
SSC-5060-2	51	57	85	141.5	16	156.75	15	1.25	15	19	2	6	68	2,000	960	118	113,100	75.6	50	1.05	5,120
SSC-6060	52	60	85	143	15	158.75	15	1.25	10	15.9	1	6	68	2,000	960	58.9	56,540	45.1	85.4	1.07	9,085
SSC-6060-2	52	60	83	143	15	158.75	15	1.25	15	19	2	6	68	2,000	960	118	113,100	75.6	51	1.07	9,585
SSC-7460S	66	74	83	188	25	188	20	1.5	10	15.9	1	6	92	2,000	960	58.9	56,540	61.1	80.1	1.36	8,620
SSC-7460-2*	66	74	83	188	25	188	20	1.5	10	15.9	2	6	92	2,000	960	118	113,100	64.7	75.7	1.36	9,300
SSC-7460	66	74	83	188	25	188	20	1.5	10	15.9	1	6	92	2,000	960	58.9	113,100	61.1	80.1	1.36	10,120