



Horizontal baler TYPE AVOS 88

Compact and economic solution for highest efficiency

With the horizontal baler type AVOS 88 you achieve **maximum continuity**. Whether paper, cardboard or foil - this press delivers convincing performance every day with high efficiency and cost-effectiveness. Highly compacted, fully-automatic bound bales enable space-saving storage and cost-optimized transport. Long lifetime, low energy consumption and easy handling - this machine leaves nothing to be desired.

Sebright Products, Inc.
Hopkins, Michigan, 49328, US

Phone +1-269-793-7183 . Fax +1-269-793-4022
sebweb@sebrightproducts.com . www.sebrightproducts.com



Horizontal baler TYPE AVOS 88-7,5/30

Horizontal baler TYPE AVOS 88 Technical Data

Options

You specify the details –
for an optimal setup:

- > Manual feeding hopper
- > Bale chute
- > Touch screen display

Your benefits:

- > **Savings:** Low power consumption
- > **Flexible:** Individual equipment options
- > **Space saving:** Suitable for applications with limited space
- > **Reliable:** Proven technology with more than 40 years of experience

Industry leading warranty:

- > 3 years parts & labor included
- > Years 4 & 5 available for purchase



Hydraulic hose with safety trap and
brust protection



Version with sliding belt conveyor

Overview of technology

	AVOS 88-7.5/30	AVOS 88-11/30
Machine length	157.5 inches	157.5 inches
Machine width	66 inches	66 inches
Machine height	98 inches	98 inches
Feeding hopper cross section	31.5" x 31.5"	31.5" x 31.5"
Dead weight approx.	7,920 lbs.	7,920 lbs.
Bale dimensions (W x H)	31.5" x 31.5"	31.5" x 31.5"
Bale weight* up to	550 lbs.	550 lbs.
Channel adjustment	manual	manual
Cycle time (empty)	22s	14s
Throughput @ 288 lbs/cubic yd, up to	5.2t/h	8.2t/h
Ram face psi	98.9 psi	98.9 psi ²
Motor size	10 HP	15 HP
Press force	66,000 lbs.	66,000 lbs.
Cylinder size	4" bore, 3" rod	4" bore, 3" rod

*depending on bale length and material

Valid for all machines:

Adjustable bale length; binding: 4-fold vertical;
Electrical connection: 460 volt, 3 phase, 60hz;
Fuse protection on site: 60 A

While Sebright Products, Inc. strives to make the information provided on processing of your waste or recycling stream, as timely and accurate as possible, the company makes no claims, promises, or guarantees about the accuracy, completeness, or adequacy of any of the provided information, and expressly disclaims liability for errors and omissions in the content of the information, or analysis provided to your company. It is solely the responsibility of each recipient of the information Sebright Products, Inc. has provided to satisfy itself as to the accuracy of the information provided by Sebright Products, Inc. and as to the efficacy of the product(s) for the use(s) intended.