




Screw Compactor

THE PRINCIPLE

Performing all waste disposal tasks economically

With our Screw Compactors, there's nothing that can't be broken down. Their compact design and electro-mechanical direct drive make H&G Screw Compactors completely reliable, low-maintenance machines. They are also robust, operator friendly and have a long service life. The separately driven feeding devices, specially designed by H&G, are adapted to each specific waste or recyclable fraction to guarantee smooth operation and a high throughput, even for large dimensions or special materials.

www.sebrightproducts.com

TECHNOLOGY

1. Screw Spiral
2. Main Drive Motor
3. Screw Spiral Bearing
4. Drive Pinion
5. Control unit
6. Central lubrication unit
7. Optional feeding device
8. Machine ratchet
9. Locking catch
10. Removable Container



TECHNOLOGY AND TARGET MARKET LEADERS MADE IN GERMANY

As technology and market leaders, we manufacture our products at our site in South Westphalia and supply our customers and partners in over 35 countries.



SUSTAINABLE WASTE DISPOSAL TECHNOLOGY

With up to 100% more filling weight compared to conventional hydraulic compression systems, transport capacities can be optimised and CO2 emissions cut.



OPTIMISED PROCESSES AND SMART TECHNOLOGY

By using our Screw Compactors, you will optimise your workflows, increase process stability and be able to monitor them with our innovative H&G Smart Technology




SCREW COMPACTOR X-LARGE-SIZE

WITH TWIN SHAFT WOODBREAKER

FRACTION:

Disposable Pallets, Euro Pallets, large wooden boxes, fruit boxes, furniture timbers

overall dimensions (max.) in inches



Fractions / Material Types:	Wood 23.6 - 78.7 inches big and bulky, manual infeed, loose filling (automated infeed only practicable to limited extent) [Wood-(Fruit-)Boxes, One-Way-Pallets, Europallets, Furniture Wood, Chipboard, OSB-Boards, Glue- and wood mold parts, Cable Drums, max, 47 inches, loose filling]
Variations:	Reinforced
Position of Spiral:	centered
Variations Repressing Devices:	Twin Shaft Woodbreaker, reinforced Type: 2x 5 hp (1x frequency converter) Shafts in 2.8 inches (Carrier in 0.8 inches)
Housing Dims: [Length[Depth], Width, Height, (inches)]	65 x 97 x 59
Infeed Opening (inches)	82 x 51
Main Drive, hp - rpm	Type A: 2x 15 hp - 17,3 rpm
E-Connect	3 x 400 V / N / PE / 50 Hz max. cable cross section: 50 mm²
Fuse	100 A - 125A (je nach Ausführung) all-current sensitive FI-circuit breaker Type B
Compaction (kg/m³)	190 - 300 (2 Motors)
Filling weight (lbs), 42yd³ Container/Receiver Box	
Filling weights to be understood as rough average, depends on type of main drive and material characteristics	13,000 - 19,000 (2 Motors)
Throughput depends on type of upstream feeder	yd³/h
manual infeed / Forklift-Truck	65 - 78
Tipping Device	limited practicability
System weight (lbs)	7936