



Horizontal auto-tie baler TYPE AVOS 1810 B5

Powerful and economic for
big challenges

The horizontal baler type AVOS 1810 B5 is the right choice for compacting large waste amounts.

The press ram is guided on steel rollers. When pressing fine grain or highly expansive materials the press can be equipped with a cross binding system. In combination with the optimized cutting system "OptiCut" and the use of one or two most energy-efficient, high-performance hydraulic pumps, this baler offers an impressive spectrum for applications with maximum throughputs. Furthermore, the sophisticated key transfer system (optional) guarantees the highest level of operation safety.

Sebright Products, Inc.
Hopkins, Michigan, 49328, US

Phone +1-269-793-7183 . Fax +1-269-793-4022
sebweb@sebrightproducts.com . www.sebrightproducts.com

**90 DAY MONEY BACK
GUARANTEE**



Horizontal auto-tie baler TYPE AVOS 1810 B5-90/100

Horizontal auto-tie baler

TYPE AVOS 1810 B5

Technical data

Options

You specify the details –
for an optimal setup:

- › Avermann special press ram to compact "difficult" materials
- › Optimized cutting system "OptiCut"
- › Feeding conveyor for continuous filling
- › Monitoring of wire breakage and wire end to control the binding wires
- › Cross binding
- › Press ram guided on plastic rails or steel rollers

Your benefits:

- › **Convenient handling:** Extremely large feeding hopper
- › **Powerful:** Suitable to compact very large amounts of waste and recyclable materials
- › **Reliable:** Proven technology with more than 40 years of experience

Industry leading warranty:

- › 3 years parts & labor included
- › Years 4 & 5 available for purchase

While Sebright Products, Inc. strives to make the information provided on processing of your waste or recycling stream, as timely and accurate as possible, the company makes no claims, promises, or guarantees about the accuracy, completeness, or adequacy of any of the provided information, and expressly disclaims liability for errors and omissions in the content of the information, or analysis provided to your company. It is solely the responsibility of each recipient of the information Sebright Products, Inc. has provided to satisfy itself as to the accuracy of the information provided by Sebright Products, Inc. and as to the efficacy of the product(s) for the use(s) intended.

5.20.24



Installation of AVOS 1810 B5-90/100



Press ram for cross binding

Overview of technology

AVOS 1810 B5-110/100

Machine length	441 inches (36'9")
Machine width	95 inches (7'11")
Machine height	154 inches (12'10")
Feed opening	71 inches x 39 inches
Dead weight approx.	61,600 lbs
Bale size (WxH)	43 inches x 30 inches
Bale weight* up-to	1,540 lbs
Channel adjustment	Three sides, automatic
Tank volume	264 gallons
Pump capacity	198 GPM
Cycle time	12.5 seconds
Throughput @ 288 lbs/cubic yd, up to	28.8 t/h
Throughput @ 288 lbs/cubic yd, with OptiCut, up to	40.3 t/h
Ram face psi	176 psi
Motor size	2 x 75 hp
Press force	224,809 lbs

* depending on bale length and material

Adjustable bale length: binding: 5-fold vertical;
Optional cross binding: 5-fold vertical, 3-fold horizontal;
Electrical connection: 460 volt, 3 phase, 60 Hz