



Avermann

Horizontal baler TYPE AVOS 88

Compact and economic solution for highest efficiency

With the horizontal baler type AVOS 88 you achieve maximum continuity. Whether paper, cardboard or foil - this press delivers convincing performance every day with high efficiency and cost-effectiveness. Highly compacted, fully-automatic bound bales enable space-saving storage and cost-optimized transport. Long lifetime, low energy consumption and easy handling - this machine leaves nothing to be desired.

Sebright Products, Inc.
Hopkins, Michigan, 49328, US

Phone +1-269-793-7183 . Fax +1-269-793-4022
sebweb@sebrightproducts.com . www.sebrightproducts.com



Horizontal baler TYPE AVOS 88-7,5/30

Horizontal baler TYPE AVOS 88 Technical Data

Options

You specify the details –
for an optimal setup:

- › Manual feeding hopper
- › Bale chute
- › Touch screen display

Your benefits:

- › **Savings:** Low power consumption
- › **Flexible:** Individual equipment options
- › **Space saving:** Suitable for applications with limited space
- › **Reliable:** Proven technology with more than 40 years of experience

Industry leading warranty:

- › 3 years parts & labor included
- › Years 4 & 5 available for purchase



Hydraulic hose with safety trap and burst protection



Version with sliding belt conveyor

Overview of technology	AVOS 88-7.5/30	AVOS 88-11/30
Machine length	157.5 inches	157.5 inches
Machine width	66 inches	66 inches
Machine height	98 inches	98 inches
Feeding hopper cross section	31.5" x 31.5"	31.5" x 31.5"
Dead weight approx.	7,936 lbs.	8,157 lbs.
Bale dimensions (W x H)	31.5" x 21.5"	31.5" x 21.5"
Bale weight* up to	550 lbs.	550 lbs.
Channel adjustment	manual	manual
Tank volume		
Cycle time (empty)	22seconds	14seconds
Throughput @ 288 lbs/cubic yd, up to	5.2t/h	8.2t/h
Ram face psi	114 psi	114 psi
Motor size	10 HP	15 HP
Press force	66,000 lbs.	66,000 lbs.
Cylinder size	4" bore, 3" rod (externally mounted)	4" bore, 3" rod (externally mounted)

*depending on bale length and material

Valid for all machines:

Adjustable bale length: binding: 4-fold vertical;
Electrical connection: 460 volt, 3 phase, 60hz;
Fuse protection on site: 60A