THE BEAST HIGH DENSITY EXTRUDER

THE OPTIMUM DEWATERING SOLUTION FOR **HIGH VOLUME** PAPER MILL WASTE STREAMS

- Dewater up to 104 yd³/hr (80m³/hr) of rejects & waste materials
- No special metal detection equipment necessary
- No expensive wear parts





The paper industry's #1 choice in waste dewatering equipment

- Custom engineered systems & auxiliary equipment
- Rugged design, low energy, proven performance
- Backed by the **BEST** warranty in the industry
- Excellent RENTAL & LEASING program available
- Over 500 installations worldwide




Features

- Extra heavy duty construction
- Times pressured management for superior dewatering
- Automated dewatering control system/ADCS
- Extra long, fully perforated dewatering chamber
- Self-relieving discharge, non-jamming design
- Customized auxiliary equipment to meet all your needs

Operational Benefits

- Dewater, compact and fill a refuse container with ONE machine
- Achieve final solids levels up to 70%
- Reduce waste disposal costs by over 50%
- Optimum performance compared to any press of its kind
- Convert wet waste into burnable fuel source
- Take control of saftey & environmental liabilities





Timed pressure management for superior dewatering performance

Only Sebright Products offers the benefit of a time managed compression cyle. Incremental increase of the ram force over time allows optimum dewatering performance. Others that use simple reciprocating ram cycles cannot achieve the superior results of the High Density Extruder.

Proprietary PLC operated ADCS


Automated Dewatering Control System


Our PLC monitors & maintains both the compression ram and the discharge restritor plate pressures. Proprietary control logic (ADCS) automatically controls the restrictor plate hydraulic pressure to allow material to discharge after dewatering and compression parameters are attained. This allows a wide range of material to be dewatered without additional operator attention.

7860XS-2-8-36

- Heavy weight construction over 26 TONS of dewatering capabilities
- 36 inch tall ram assembly
- 36 yd³ (27.5 m³) feed chamber volume







* All dimensional data for reference only

* Due to product improvement, the manufacturer reserves the right to alter, or amend, without notice, any of these specifications and dimensions.



Where can you find the High Density Extruder?

Graphic Packaging Sonoco Products Greif Fabrica de Papei Cartones America Papelera del Sur Sonoco Brazil Sonoco Canada Pratt Industries
Ox Industries
Anhui Shanying Paper
Chenming Paper
Packaging Corp. of America
Cascades
Kimberly Clark Corp.
Nine Dragons Paper

WestRock
Georgia Pacific Corp.
Huhtamaki
Essity N.A.
US Gypsum
International Paper
NORPAC
and many others...

While Sebright Products, Inc., strives to make the information provided on processing of your waste or recycling stream, as timely and accurate as possible, the company makes no claims, promises or guarantees about the accuracy, completeness, or adequacy of any of the provided information, and expressly disclaims liability of errors and omissions in the content of the information, or analysis provided to your company. It is solely the responsibility of each recipient of the information Sebright Products, Inc., has provided to satisfy itself as to the accuracy of the information provided by Sebright Products, Inc., and as to the efficacy of the product(s) for the use(s) intended.

7860XS-V1